

CHO-LUBE® E117

Electrically Conductive Grease

Parker Chomerics CHO-LUBE® E117 Electrically Conductive Grease is a silver-nickel filled, electrically conductive grease designed for effective anti-wear, helping to extend the life of parts and equipment on flanges and airframes.

Due to its high electrical conductivity in uncontrolled environments, it is ideal for use in harsh, critical environments such as those found in aviation or defense applications.

CHO-LUBE E117 helps to improve surface-to-surface contact while protecting from wear and tear. Consumer applications include grounding of enclosures and various equipment, screw threads for lubricating, grounding purpose, etc.

Product Features

- Long life durability
- Low resistivity
- Low viscosity for processing and wetting benefits
- Lubricating properties
- Wide temperature resistance
- Non-sagging
- Flange protection

Product Features

- Electrical contact between metallic surfaces
- Lubrication with shielding properties
- Heat dissipation
- Surface protection



CHO-LUBE® E117 Product Information

	Typical Properties	E117	Test Method
Typical Properties	Binder	Silicone	N/A
	Filler	Nickel-Silver	N/A
	Color	Beige	N/A
	Wet Density	3.1 g/ml	95-40-5504* (Q/C)
	Volume Resistivity	0.040 max. ohm-cm	CHO-MAT 1002* (Q/C)
	Shelf Life, from date of manufacture	12 months @ 77°F (25°C)	(Q)
	Continuous Use Temperature	-55 to 200°C (-131 to 392 F)	(Q)
	Minimum thickness recommended	0.001 in. (0.025 mm)	N/A
	Maximum thickness recommended	N/A	N/A
	Volatile Organic Content (VOC)	0 g/l	Calculated
Mechanical	Penetration, unworked 25C	375 (NLGI #2)	ASTM D217
	Penetration, worked 60 strokes 25C	384 (NLGI #2)	ASTM D217
	4-ball wear, 40 kg 1200 rpm	0.4 mm	ASTM D2266
	4-ball EP, weld load	400kg	ASTM D2596

Note: N/A – Not Applicable, (Q/C) - Quality Conformance Tests, (Q) - Qualification Tests
 * this test Method is available from Parker Chomerics.

CHO-LUBE® E117 Ordering Information

Product	Weight (grams)	Packaging	Part Number
CHO-LUBE E117	113.4	200g plastic container	54-01-E117-0200

Please refer to Parker Chomerics Surface Preparation and CHO-BOND Polythioether Application documents for information regarding the proper surface preparation, primer application (if required), and use of these compounds.



We're Here to Help

Scan QR code or visit parker.com/chomerics to:

- [Request a Free Sample](#)
- [Talk to an Expert](#)
- [Get a Quote](#)
- [Find Where to Buy](#)

Parker Hannifin Corporation
Chomerics Division
 77 Dragon Court
 Woburn, MA 01801
 Phone 781 935 4850
 Fax 781 933 4318
chomailbox@parker.com
parker.com/chomerics

CHODS1239 March 2026

©2026 Parker Hannifin Corporation

